NUVONIC

formerly Aquionics, Berson, Hanovia and Orca GmbH



SwimLine Splash PH

UV TREATMENT FOR POOLS AND SPAS

Our **SwimLine Splash PH** UV systems provide effective chloramine removal and treatment for all leisure facilities, from spas to large competition pools. They break down monochloramine, di- and trichloramine, which are responsible for eye and skin irritation, headaches and unpleasant odours.

UV also has the added advantage of deactivating chlorine resistant Cryptosporidium and is up to 5 times cheaper to maintain and occupies only 1/10th of the space of ozonation equipment.

Application Optimised UV for Pools & Leisure

SWIMLINE SPLASH PH™ - SINGLE POOL WITH UV TREATMENT



KEY FEATURES	WHAT IT GIVES YOU	BENEFITS FOR YOU
INTELLIGENCE		
*UV intensity monitor	Continuous verification of performance with in-built low intensity or dose alarm	Easy to monitor and log system performance
Flow meter input	Real time adjustment of lamp power based on flow, if *UV monitor and *Power stepping are added.	Saves power
OPTIMISATION		
Medium pressure lamp	Provides UV light at 200 to 400 nm wavelengths ideal for the destruction of mono-, di- and trichloramine	Visibly clear water with reduced odours
		Reduced building corrosion risk
		Minimises bathers' eye and skin irritation
	Provides active wavelengths to treat the water	Protects bathers from chlorine resistant Cryptosporidium and Giardia
	*Automatic wiper (quartz cleaning)	Self cleaning
INTEGRATION		
Designed specifically for pools	UV Disconnect power cut-out for lamp access (option)	Enhanced operator safety when changing a lamp
	Water leak detection (option)	Increased bather safety when used with a strainer

*Option



MODEL NUMBER	MAX POWER (KW)	MIN UVT (%)	DIMENSIONS (MM)									APPROX WEIGHT (KG)	
			A	B	C	D	E	DN	K*	L	M**	Chamber (Empty)	Control Cabinet
SwimLine Splash PH 60	1.6	85	850	240	320	240	400	80	330	750	850	40	85
SwimLine Splash PH 70	1.6	85	850	240	320	240	400	100	330	750	850	45	85
SwimLine Splash PH 120	2.7	78	1300	660	320	240	400	150	330	750	850	50	85
SwimLine Splash PH 195	4.4	81	1300	660	320	240	400	150	330	750	850	50	85
SwimLine Splash PH 295	4.4	90	1300	610	420	290	550	200	330	750	850	75	85
SwimLine Splash PH 470	5.8	84	1300	610	420	290	550	200	330	900	1100	75	165
SwimLine Splash PH 600	5.8	93	1300	550	505	410	600	250	330	900	1100	120	165
SwimLine Splash PH 705	5.8	93	1800	960	505	410	600	300	330	900	1100	160	165
SwimLine Splash PH 850	12.5	62	1800	960	505	410	600	300	330	1100	1600	160	270
SwimLine Splash PH 990	16.5	76	1800	930	540	430	650	350	330	1100	1600	200	282

All dimensions are approximate for clearance purposes only. We have a policy of continuous product development, exact drawings are available on request.
All specifications are subject to change without notification. Your distributor or our account manager can advise on correct sizing and specification requirements.
* Allow dimension L in front of cabinet for door opening and panel access.
** M dimension includes the space for the cabinet mounting brackets but you need to allow space below the cabinet for cable entry and access (minimum of 250 mm).

UV CHAMBER

Material:	Stainless steel 316L / 1.4404
Internal finish:	As made pipe and tube, welds as laid, electropolished and passivated
External finish:	Sateen polish (120 grit) electropolished and passivated
Process (mating) connections:	Flange EN 1092-1 PN16
Drain connection:	BSPT or NPT if ANSI flange
End plate:	Removable end plate
Degree of protection:	IP65 equivalent to NEMA 4 but not for outside use
Arc tube (lamp):	Medium pressure
Arc tube enclosure:	Pure quartz (F200)
Number of arc tubes (lamps):	1 (Splash PH 60-705) 3 (Splash PH 850) 4 (Splash PH 990)
Expected lamp life:	8000 hours
Temperature sensor:	Yes
Working fluid temperature:	1°C to 60°C
Hydrostatically pressure tested:	Yes to PED requirements EN 13445
Chamber mounting:	Horizontal only
Operating pressure:	6 bar (positive pressure only)
Pressure loss:	Typically < 70 mbar
Seals:	EPDM

OPTIONS

- Operation and Maintenance manual and printed Installation and Commissioning manual in Chinese, English, French, German and Spanish
- Flange options: ANSI 150 (with NPT drain), JIS, Table 'E'
- Wiper: automatic (electrically driven)
- Strainer
- UV monitor: wet UV monitor (to minimum UVT)
- Power adjustment: 4 level power stepping
- Lead length: 20 m, 30 m or 50 m cabinet to chamber
- Skid mounting (not shipboard or earthquake zone)
- Air vent connection: BSPT or NPT if ANSI flange

OPTIONS (CONTINUED)

- Aggressive water package: For 400 ppm to 20000 ppm chloride water
- UV Disconnect: Power cut-out for lamp access
- Water leak detection: Detects water leaks from quartz sleeve
- Chamber configuration: S shape

CABINET (CONTROLLER PHOTON)

Material:	Polyester coated carbon steel
Degree of protection:	IP54 NEMA 12
Supply voltages (nominal):	Splash PH 60-120 95 V to 260V (+/-10%) Splash PH 195-705 190 V to 480 V (+/-10%) Splash PH 850-990 380 V to 480 V (+/-10%) 50/60 Hz
Operating temperature range:	5°C to 40°C
Relative humidity:	<85% non-condensing
Cooling fans:	Yes
Interconnecting cable:	10 m cabinet to chamber

CUSTOMER OUTPUTS

4-20 mA passive or active outputs:	UV intensity, or UV dose if Power stepping option is added
VFC outputs:	System warning, lamp ready, low UV, common trip, remote reset, ELCB or water leak, system available, local or remote mode

CUSTOMER INPUTS

4-20 mA passive or active input:	Flow meter
VFC inputs:	Remote stop/start and remote reset

CUSTOMER COMMUNICATIONS PORT

None

APPROVALS

CE marked, UL listed E 149108

SwimLine PH

Also available in our Pools & Leisure product range...

SWIMLINE PH

3rd party validated systems for critical treatment and dechloramination

Canada
+1 980 256 5700
americas@nuvonicuv.com

China
+86 21 6167 9599
apac@nuvonicuv.com

Germany
+49 2268 90 8300
germany@nuvonicuv.com

Mexico
+1 980 256 5700
americas@nuvonicuv.com

United Kingdom
+44 175 351 5300
emea@nuvonicuv.com

USA
+1 980 256 5700
americas@nuvonicuv.com

NUVONIC

A Halma company

formerly Aquionics, Berson, Hanovia and Orca GmbH

©2023 Nuvonic 910430-4700-02-EN

nuvonic.com

FM 29365